



Standard load delivery:  
**22 towers per truck**

NOTE: Tower is supplied non-dressed, meaning that user must supply & fit their own security monitoring equipment.



**HYBRID POWERED**

## Static Security Tower

When looking for an advanced, industry suited, static security tower, look no further than our **X-PROTECTION**

FEATURES	BENEFITS
» Non dressed head...	... ready to support your choice of security/ monitoring equipment
» 5m vertical hydraulic mast...	... for quick and simple erection
» 22 towers to one truck...	... simplifying transport & storage
» Hybrid power pack with high level batteries and a back up generator with extremely lower consumption ...	... up to 6 months autonomous without refueling ( based on 24hrs / days running time)

 Your security equipment here (not included)

 Safe store security equipment here



## Specifications

Mast	
Lifting Method	Manual
Max Mast Height	5 m
Rotation	no
Safety brake	mechanical

Battery	
Type	AGM
N°	4
Power battery pack	24VDC – 400 Ah
Expected battery cycle	500

Engine	
Model	Kubota Z482 StageV
Layout	2-cylinders, 479 cm <sup>3</sup>
Rpm	@1500 rpm
Fuel consumption	0.5 l/hr

Alternator	
Model	Linz Electric
Rated output	3.5 kVA
Frequency	50Hz
Voltage	220V

Running Time	
<i>Based on 100W of power consumption</i>	
Running Time, only battery	75 hrs
Total running time before refilling	4663 hrs

Dimensions	
Transport dimensions (mm) LxWxH	1150x1150x2492h
Dimensions in operation (mm) LxWxH	2350x2350x6000h
Fuel tank	203 l
Dry weight	1200 Kg

Safety brake on manual winch

### Hardware options

To find out about our hardware options please contact our sales team on **+39 0382 406252**